

# InteliVision 5.2



Order code: RD2IV5BxBAA

## 5" display for ComAp controllers

# Datasheet

## Product description

InteliVision 5.2 is an industrial 5" remote colour display for ComAp controllers. It is designed as an easy-to-use Plug&Play display for monitoring and control of single gen-set in various applications.


## Key features

- ▶ 5" colour screen with resolution of 800 × 480 pixels
- ▶ Plug & Play operation
- ▶ Possibility of screens customization (Screen Editor)
- ▶ 5 configurable user buttons under the screen
- ▶ Modern look and graphical user interface
- ▶ Trends monitoring screen (up to 4 channels)
- ▶ Communication with controller via Ethernet
- ▶ Operating temperature: -30 °C to +70 °C  
(-40 °C to +70 °C if the device is powered on above -30 °C)
- ▶ Front protection compliant with IP65
- ▶ 1x Analog Input, 1x Binary Output

## Related products

- ▶ InteliGen 500

## Application overview



## Technical data

### Power supply

Power supply range	8-36 VDC
Power consumption (typical values)	6 W (Actual consumption depends on LCD backlight intensity and actual CPU consumption.)

### Operating conditions

Operating temperature	-30 °C to +70 °C (-40 °C to +70 °C)*
Storage temperature	-30 °C to +80 °C
Front panel protection	IP65
Humidity	95 % non-condensing (EN 60068-2-30)
Vibration	5-25 Hz, $\pm 1.6$ mm 25-100 Hz, a = 4 g
Shocks	a = 500 m/s <sup>2</sup>
Surrounding air temperature rating 70 °C.	
Suitable for pollution degree 2.	

**Note:** \*) Device must be powered on above -30 °C to operate at temperatures to -40 °C.

### Interfaces

Ethernet port	10/100 Mbit RJ45
RS-485	Not used
CAN	Not used
USB Device	Non-isolated type B connector
USB Host	Non-isolated type A connector

### Analog inputs

Resistive input	R = 0-2400 $\Omega$ R: $\pm 2$ % from value $\pm 5$ $\Omega$ for 0-250 $\Omega$ R: $\pm 4$ % from value for 250-2400 $\Omega$ (Dedicated for external LCD backlight control, 5-2400 $\Omega$ corresponds to 0-100% backlight)
-----------------	--

### Binary outputs

Specification	1x, Non-Isolated max. 0.5 A (Active when controller's Hom output is activated)
---------------	--


### LCD specification

LCD panel	TFT 5"
Resolution	800 × 480 px

### Mechanical

Housing	Plastic
Mounting	4 clips
Recommended cut-out	187 × 132 mm (7.362 × 5.196 in)

## Dimensions, terminals and mounting





**Note:** IntelVision 5.2 can be mounted into the panel doors. Four holders are used for Display unit mounting. The recommended cut-out dimension for the unit is 187 mm × 132 mm (7.362 in × 5.196 in), approximately 2 mm wider than the unit size on each side.

## Related products

Product	Description	Order code
InteliGen 500	ComAp's advanced paralleling gen-set controller with 5" colour display.	<a href="#">IG3500XXBAA</a>

## Certificates and standards

<ul style="list-style-type: none"> <li>▶ EN 61000-6-2</li> <li>▶ EN 61000-6-4</li> <li>▶ EN 60068-2-1 (-20 °C/16h)</li> <li>▶ EN 60068-2-2 (70 °C/16h)</li> <li>▶ EN 60068-2-6 (2-25 Hz/±1.6mm; 25-100 Hz / 4.0 g)</li> <li>▶ EN 60068-2-27 (a=500 /m<sup>2</sup>; T=6 ms)</li> <li>▶ EN 60068-2-30:2005 25/55°C, RH 95%, 48hours</li> <li>▶ EN 60529 (front panel IP65, back side IP20)</li> <li>▶ UL 6200</li> </ul>	 
<p>List of standards is available on: <a href="https://webstore.iec.ch/">https://webstore.iec.ch/</a></p>	

