RUBIA D





MULTIGRADE OIL FOR DIESEL ENGINES

USES

- TOTAL RUBIA D is also suitable for turbocharged or normally aspirated Diesel engines of construction machinery! Earth moving machinery. Commercial road transport, of highway vehicles High Speed Diesel Engine. Generator Sets, Fishing boat etc.

PROPERTIES

- Multigrade.
- High viscosity index.
- Exceptional detergency level.
- Very high dispersancy level.

- High stability in operation.
- Excellent antiwear and anticorrosion properties.
- Excellent antioxidant, antirust and antifoaming properties.

CHARACTERISTICS

RUBIA D	Units	SAE Grades 20W-50
Volumetric mass at 15°C	kg/m ³	900
Viscosity at 40°C	mm²/s	168.8
Viscosity at 100°C	mm²/s	19.22
Viscosity index	-	130
Flash point Cleveland	°C	190
Pour point	°C	-21
TBN		12.5

The typical characteristics are given as a guide only

SPECIFICATIONS

API CF/CD/SF MERCEDES BENZ 227.0
MIL-L-2104 E MAN 270

MIL-L-46152 B/C CATERPILLAR TO-2

CCMC D2 ALLISON C-4
ACEA E 1-96 KOMATSU
PIELSTICK