

Generator set data sheet

Model: C1000 D5
 Frequency: 50
 Fuel type: Diesel

Spec sheet:	SS14-CPGK
Noise data sheet (open/enclosed):	ND50-OSHHP/ND50-CS550
Cooling system data:	MCP-1037

Fuel consumption	Standby				Prime			
	kVA (kW)				kVA (kW)			
Ratings	1041 (833)				939 (751)			
Load	1/4	1/2	3/4	Full	1/4	1/2	3/4	Full
gph	14.6	27.7	40.7	53.9	13.4	24.7	36.6	48.5
L/hr	55	105	154	204	51	94	139	184

Engine	Standby Rating	Prime Rating
Engine manufacturer	Cummins	
Engine model	QST30-G3	
Configuration	Cast iron, 50 ° V12 cylinder	
Aspiration	Turbocharged and after-cooled	
Gross engine power output, kWm	895	806
BMEP at set rated load, kPa	2358	2117
Bore, mm	140	
Stroke, mm	165	
Rated speed, rpm	1500	
Piston speed, m/s	8.3	
Compression ratio	14:1	
Lube oil capacity, L	133	
Overspeed limit, rpm	1725 ±50	
Regenerative power, kW	58	
Governor type	Electronic	
Starting voltage	24 Volts DC	

Fuel flow

Maximum fuel flow, L/hr	550
Maximum fuel inlet restriction, mm Hg	203
Maximum fuel inlet temperature, °C	66

Air	Standby Rating	Prime Rating
Combustion air, m ³ /min	56.1	51.9
Maximum air cleaner restriction, kPa	6.2	

Exhaust

Exhaust gas flow at set rated load, m ³ /min	163	146
Exhaust gas temperature, °C	563	541
Maximum exhaust back pressure, kPa	10.2	

Standard set-mounted radiator cooling

Ambient design, °C	40	
Fan load, kW _m	18	
Coolant capacity (with radiator), L	169	
Cooling system air flow, m ³ /sec @ 12.7 mmH ₂ O	15.5	
Total heat rejection, Btu/min	22970	21200
Maximum cooling air flow static restriction mm H ₂ O	12.7	

Weights*

	Open	Enclosed
Unit dry weight kgs	6246	RTF
Unit wet weight kgs	6426	RTF


* Weights represent a set with standard features. See outline drawing for weights of other configurations.

Dimensions


	Length	Width	Height
Standard open set dimensions mm	4302	1702	2139
Enclosed set standard dimensions mm	RTF	RTF	RTF

Genset outline

Open set



Enclosed set



Outlines are for illustrative purposes only. Please refer to the genset outline drawing for an exact representation of this model.

Alternator data

Connection	Temp rise °C	Duty	Alternator	Voltage
Wye, 3-phase	150/125 C	S/P	HC6J	380-440V

Ratings definitions

Emergency standby power (ESP):	Limited-time running power (LTP):	Prime power (PRP):	Base load (continuous) power (COP):
Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. Emergency Standby Power (ESP) is in accordance with ISO 8528. Fuel Stop power in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power to a constant electrical load for limited hours. Limited Time Running Power (LTP) is in accordance with ISO 8528.	Applicable for supplying power to varying electrical load for unlimited hours. Prime Power (PRP) is in accordance with ISO 8528. Ten percent overload capability is available in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power continuously to a constant electrical load for unlimited hours. Continuous Power (COP) is in accordance with ISO 8528, ISO 3046, AS 2789, DIN 6271 and BS 5514.

Formulas for calculating full load currents:

Three phase output

$$\frac{\text{kW} \times 1000}{\text{Voltage} \times 1.73 \times 0.8}$$

Single phase output

$$\frac{\text{kW} \times \text{SinglePhaseFactor} \times 1000}{\text{Voltage}}$$

See your distributor for more information.

Cummins Power Generation
 Manston Park, Columbus Avenue
 Manston, Ramsgate
 Kent CT12 5BF, UK
 Telephone: +44 (0) 1843 255000
 Fax +44 (0) 1843 255902
 E-mail: cpg.uk@cummins.com
 Web: www.cumminspower.com

