



Product Specifications

LF9070



Lube, Spin-On

Fleetguard® LF9070 premium lube combo spin-on filter combines full-flow and by-pass filtration into one single filter developed to meet or exceed engine requirements. This unique arrangement of filtration provides the perfect balance between efficiency and low restriction to oil flow.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Media Type	Others	Thread Size	M95 X 2.5-7H INT
Length	13.88 inch	Largest OD	4.74 inch
Gasket Inside Diameter	4.00 inch	Gasket OD	4.74 inch
Hydrostatic Burst Minimum	299.918 psi	Pressure Valve	No
Rated Flow	150 L/m		

Product Comments

Venturi Combo Filter with Stratapore media

Related Parts

Replaces LF9000

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2024 Cummins Filtration Inc. All Rights Reserved