

Product Specifications



P553200 FUEL FILTER, WATER SEPARATOR SPIN-ON

Why Choose Donaldson Fuel Filters?

Donaldson fuel filters are designed to help prevent premature injector and pump wear by delivering cleaner fuel to your engines.

• Versatile – no keys necessary for installation; universal interface allows one part to fit multiple applications.

• Integrated hose barb allows attaching a hose to drain water to a container.

• Fully compatible with OEM accessories such as water collection bowls, drain valves, and water-in-fuel (WIF) sensors.

Outer Diameter	4.65 inch (118 mm)
Thread Size	1 1/4-12 UN
Length	10.04 inch (255 mm)
Gasket OD	4.37 inch (111 mm)
Gasket ID	3.84 inch (97.5 mm)
Bowl Thread	3 3/4-10 UN
Efficiency Beta 75	10 micron

Attributes

Efficiency Test Std	ISO 4548-12, JIS D 1617
Collapse Burst	100 psi (6.9 bar)
Туре	Water Separator
Style	Spin-On
Primary Application	KOMATSU 6003114510
Notes	Not for Marine Applications
Packaged Dimensions	
Packaged Length	0.13 M
Packaged Width	0.13 M
Packaged Height	0.27M
Packaged Weight	1.4 KG
Packaged Volume	0.0046 M3
Other Information	
Country of Origin	Indonesia
NMFC Code	121510
HTS Code	8421230000
UPC Code	742330186732

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.