



Product Specifications

FF5018



Fuel, Spin-On

Fleetguard® FF5018 spin-on fuel filter delivers superior performance using proven media technology, removing harmful contaminants. Fleetguard fuel filters ensure optimal fuel system protection to meet or exceed OEM specifications.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Thread Size	M16 X 1.5-6H INT	Gasket Inside Diameter	2.44 inch
Gasket OD	2.76 inch	Length	4.92 inch
Largest OD	3.05 inch	Standpipe	YES
Primary Particle Efficiency	17 micron (c) @ 98.7%		

Related Parts

Replaces	FF42000	FF4013
For Upgrade, Use	FS1221	
Is Metal Version Of	FF42000	
Filter Used With	3311505S	
For Stratapore Version, Use	FF5461	

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved