



Product Specifications

FS53014

Fuel/Water Separator



Fleetguard® FS53014 Elemax™ stacked filter removes harmful contaminants improving reliability, service intervals and fuel efficiencies, and reducing costs. Its patented control valve provides more complete use of the filter and has multiple micron ratings for OEM compliance and biodiesel compatible.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Media Type	NanoNet	Largest OD	5.83 inch
Largest End ID	1.54 inch	Length	16.20 inch
Gasket Inside Diameter	1.49 inch	Gasket OD	1.63 inch
Flow Direction	Outside In	Length / Overall Height	16.20 inch

Product Comments

Used on FH239 Series Industrial Pro

Related Parts

FH23903	FH23914	FH23920	FH23913
FH23930	FH23906	FH23907	FH23908

Uses

Element	FH23915	FH23918	FH23910	FH23921
	FH23911	FH23923	FH23922	FH23919
	FH23912	FH23905	FH23901	

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved