



Product Specifications

LF691A



Lube, Full-Flow Spin-On

Fleetguard® LF691A spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Thread Size	1 1/2-16 UNS-2B	Gasket OD	4.29 inch
Gasket Inside Diameter	3.72 inch	Length	12.19 inch
Largest OD	5.38 inch	Hydrostatic Burst Minimum	199.95499999999998 psi
Rated Flow	106 L/m		

Related Parts

For Upgrade, Use	LF9691A	LF3566
Uses Service Part	3838290S	
Replaces	LF3954	

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or

non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved