

Product Specifications



P557780 LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

• Keep oil clean by capturing contaminants that cause engine damage.

• Include heavy duty components that are built to perform, built to last.

• Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	93 mm (3.66 inch)
Thread Size	3/4-16 UN
Length	136 mm (5.35 inch)
Gasket OD	71 mm (2.80 inch)
Gasket ID	61 mm (2.40 inch)
Efficiency 99%	40 micron
Anti-Drainback Valve	Yes
Bypass Valve	Yes
Bypass Valve Setting LR	0.75 bar (11 psi)

Bypass Valve Setting HR	1.2 bar (17 psi)
Media Type	Cellulose
Collapse Burst	13.8 bar (200 psi)
Туре	Full-Flow
Style	Spin-On
Packaged Dimensions	
Packaged Length	3.7 IN
Packaged Width	3.7 IN

1.25 LB

0.0396 FT3

Other Information	
Country of Origin	Poland
NMFC Code	133320
HTS Code	8421230090
UPC Code	742330045466
EU Preferential Origin	Yes

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.

Packaged Weight

Packaged Volume