



Product Specifications

LF3548



Lube, Combination

Fleetguard® LF3548 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

| | | | |
|------------------------------|-------------------|--------------------------------|------------------------|
| Thread Size | 2.25-12 UNF 2B | Gasket OD | 4.68 inch |
| Gasket Inside Diameter | 4.01 inch | Largest OD | 4.68 inch |
| Length | 9.36 inch | Efficiency Test Std | SAE J1858 |
| Hydrostatic Burst Minimum | 275.935 psi | Primary Particle Efficiency | 30 micron (c) @ 98% |
| Rated Flow | 75.2 L/m | | |

Related Parts

For Upgrade, Use LF9548

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor

completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved