



Product Specifications

LF3625



Lube, Spin-On

Fleetguard® LF3625 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Thread Size	1-12 UNF 2B	Largest OD	3.66 inch
Length	8.52 inch	Gasket Inside Diameter	2.44 inch
Gasket OD	2.76 inch	Media Type	Cellulose
Hydrostatic Burst Minimum	217.4999999999997 psi	Pressure Valve	Yes
Rated Flow	60 L/m	Primary Particle Efficiency	50 micron (c) @ 95%

Product Comments

Same as LF4054 with a removal nut welded on shell

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or

non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved