



Product Specifications

LF17556



Lube

Fleetguard® LF17556 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Gasket OD	3.50 inch	Media Type	Cellulose
Gasket Inside Diameter	3.19 inch	Largest OD	3.66 inch
Hydrostatic Burst Minimum	242.005 psi	Rated Flow	20 L/m
Length	6.54 in	Thread Size	M22X1.5-6H
Primary Particle Efficiency	38 micron (c) @ 98.7%		

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the

exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved