

## **Product Specifications**



## P550947

## LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

## **Attributes**

Outer Diameter	119 mm (4.69 inch)
Thread Size	1 1/2-12 UN
Length	160 mm (6.30 inch)
Gasket OD	110 mm (4.33 inch)
Gasket ID	98 mm (3.86 inch)
Efficiency 99%	21 micron
Efficiency Test Std	SAE J1858
Media Type	Cellulose
Collapse Burst	10.3 bar (149 psi)
Efficiency 99% Efficiency Test Std Media Type	21 micron  SAE J1858  Cellulose

Туре	Full-Flow
Style	Spin-On
Primary Application	DETROIT DIESEL 25011106
Packaged Dimensions	
Packaged Length	0.115824 M
Packaged Width	0.115824 M
Packaged Height	0.155448M
Packaged Weight	0.9842954429 KG
Packaged Volume	0.0021152684 M3
Other Information	
Country of Origin	Poland
NMFC Code	069095-02
HTS Code	8421230090
UPC Code	742330043424
EU Preferential Origin	Yes

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.