



P502413

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	107 mm (4.21 inch)
Thread Size	1-12
Length	150 mm (5.91 inch)
Gasket OD	98.2 mm (3.87 inch)
Gasket ID	87.6 mm (3.45 inch)
Efficiency 50%	10 micron
Efficiency 95%	20 micron
Efficiency 99%	40 micron
Efficiency Test Std	ISO 4548-12, JIS D 1611

Anti-Drainback Valve	Yes
Media Type	Cellulose
Collapse Burst	6.9 bar (100 psi)
Type	Full-Flow
Style	Spin-On
Primary Application	HINO 156072250

Packaged Dimensions

Packaged Length	0.11 M
Packaged Width	0.11 M
Packaged Height	0.16M
Packaged Weight	0.76 KG
Packaged Volume	0.001936 M3

Other Information

Country of Origin	Indonesia
HTS Code	8421230090
UPC Code	742330196731
EU Preferential Origin	No

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.