



P502458

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	102 mm (4.02 inch)
Thread Size	1-12 UN
Length	101 mm (3.98 inch)
Gasket OD	99 mm (3.90 inch)
Gasket ID	88 mm (3.46 inch)
Efficiency 50%	17 micron
Efficiency 95%	27 micron
Efficiency 99%	39 micron
Efficiency Test Std	ISO 4548-12

Anti-Drainback Valve	Yes
Bypass Valve	Yes
Bypass Valve Setting LR	1 bar (15 psi)
Media Type	Cellulose
Collapse Burst	6.9 bar (100 psi)
Type	Full-Flow
Style	Spin-On
Primary Application	MITSUBISHI 32A4000400

Packaged Dimensions

Packaged Length	0.1 M
Packaged Width	0.1 M
Packaged Height	0.12M
Packaged Weight	0.69 KG
Packaged Volume	0.0012 M3

Other Information

Country of Origin	Türkiye
HTS Code	8421230090
UPC Code	742330202708
EU Preferential Origin	No

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the

actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.