



## P550086

### LUBE FILTER, SPIN-ON FULL FLOW

#### Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

#### Attributes

Outer Diameter	108 mm (4.25 inch)
Thread Size	1 1/8-16 UN
Length	167 mm (6.57 inch)
Gasket OD	99 mm (3.90 inch)
Gasket ID	90 mm (3.54 inch)
Efficiency 50%	20 micron
Efficiency Test Std	ISO 4572
Bypass Valve	Yes
Bypass Valve Setting LR	1.8 bar (26 psi)

Bypass Valve Setting HR	2.1 bar (30 psi)
Media Type	Cellulose
Collapse Burst	10 bar (145 psi)
Type	Full-Flow
Style	Spin-On
Primary Application	KOMATSU 6136515120

---

#### Packaged Dimensions

Packaged Length	4.2 IN
Packaged Width	4.2 IN
Packaged Height	6.75IN
Packaged Weight	1.92 LB
Packaged Volume	0.0689 FT3

---

#### Other Information

Country of Origin	Mexico
NMFC Code	069100-06
HTS Code	8421230090
UPC Code	742330040768
EU Preferential Origin	No

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that

accompanies the goods.