

## **Product Specifications**



## P550341

## LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

## **Attributes**

Outer Diameter	141 mm (5.55 inch)
Thread Size	1 1/2-16 UN
Length	310 mm (12.20 inch)
Gasket OD	111 mm (4.37 inch)
Gasket ID	100 mm (3.94 inch)
Efficiency 50%	25 micron
Efficiency Test Std	SAE J1858
Bypass Valve	Yes
Bypass Valve Setting LR	2.2 bar (32 psi)

Bypass Valve Setting HR	2.8 bar (41 psi)
Media Type	Cellulose
Collapse Burst	4.1 bar (59 psi)
Туре	Full-Flow
Style	Spin-On
Primary Application	DAF 267714
Packaged Dimensions	
Packaged Length	0.14 M
Packaged Width	0.14 M
Packaged Height	0.33M
Packaged Weight	1.95667 KG
Packaged Volume	0.00646 M3
Other Information	
Country of Origin	Poland
NMFC Code	069100-09
HTS Code	8421230090
UPC Code	742330042243
EU Preferential Origin	Yes

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that

