

Product Specifications



P550758

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	93 mm (3.66 inch)
Thread Size	M24 x 1.5
Length	136 mm (5.35 inch)
Gasket OD	72 mm (2.83 inch)
Gasket ID	62 mm (2.44 inch)
Efficiency 99%	40 micron
Bypass Valve	Yes
Bypass Valve Setting LR	1.2 bar (17 psi)
Bypass Valve Setting HR	1.6 bar (23 psi)

Media Type	Cellulose
Collapse Burst	10 bar (145 psi)
Туре	Full-Flow
Style	Spin-On
Primary Application	JOHN DEERE RE519626
Packaged Dimensions	
Packaged Length	3.6 IN
Packaged Width	3.6 IN
Packaged Height	5.4IN
Packaged Weight	1.07 LB
Packaged Volume	0.0405 FT3
Other Information	
Country of Origin	Mexico
NMFC Code	069100-09
HTS Code	8421230090
UPC Code	742330167656
EU Preferential Origin	No

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.