



P550942

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	93 mm (3.66 inch)
Thread Size	3/4-16 UN
Length	107 mm (4.21 inch)
Gasket OD	72 mm (2.83 inch)
Gasket ID	62 mm (2.44 inch)
Efficiency 99%	40 micron
Efficiency Test Std	ISO 16889
Anti-Drainback Valve	Yes
Bypass Valve	Yes

Bypass Valve Setting LR	2.3 bar (33 psi)
Bypass Valve Setting HR	2.6 bar (38 psi)
Media Type	Cellulose
Type	Full-Flow
Style	Spin-On
Primary Application	KUBOTA 1540232090

Packaged Dimensions

Packaged Length	3.7 IN
Packaged Width	5 IN
Packaged Height	4IN
Packaged Weight	0.975 LB
Packaged Volume	0.042772 FT3

Other Information

Country of Origin	Mexico
NMFC Code	069100-06
HTS Code	8421230090
UPC Code	742330200759
EU Preferential Origin	No

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that

accompanies the goods.