

Product Specifications



P551343

LUBE FILTER, SPIN-ON COMBINATION

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.

Attributes

Outer Diameter	108 mm (4.25 inch)
Thread Size	M26 x 1.5
Length	135 mm (5.31 inch)
Gasket OD	73 mm (2.87 inch)
Gasket ID	56 mm (2.20 inch)
Efficiency 50%	16 micron
Efficiency Test Std	JIS D 1611
Anti-Drainback Valve	Yes
Bypass Valve	Yes
Bypass Valve Setting LR	0.5 bar (7 psi)

Bypass Valve Setting HR	0.7 bar (10 psi)
Media Type	Cellulose
Collapse Burst	6.9 bar (100 psi)
Туре	Combination
Style	Spin-On
Primary Application	MITSUBISHI MD069782
Packaged Dimensions	
Packaged Length	4.6 IN
Packaged Width	4.7 IN
Packaged Height	5.3IN
Packaged Weight	1.99 LB
Packaged Volume	0.0663 FT3
Other Information	
Country of Origin	Colombia
NMFC Code	121260
HTS Code	8421230090
UPC Code	742330106983
EU Preferential Origin	No

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that

