



P551604

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	108 mm (4.25 inch)
Thread Size	1-12
Length	232 mm (9.13 inch)
Gasket OD	71 mm (2.80 inch)
Gasket ID	62 mm (2.44 inch)
Efficiency 50%	14 micron
Efficiency Test Std	SAE J1858
Anti-Drainback Valve	Yes
Bypass Valve	Yes

Bypass Valve Setting LR	1.3 bar (19 psi)
-------------------------	------------------

Bypass Valve Setting HR	1.4 bar (20 psi)
-------------------------	------------------

Media Type	Cellulose
------------	-----------

Collapse Burst	6.9 bar (100 psi)
----------------	-------------------

Type	Full-Flow
------	-----------

Style	Spin-On
-------	---------

Packaged Dimensions

Packaged Length	0.37 FT
-----------------	---------

Packaged Width	0.37 FT
----------------	---------

Packaged Height	0.79FT
-----------------	--------

Packaged Weight	2.35 LB
-----------------	---------

Packaged Volume	0.1064 FT3
-----------------	------------

Other Information

Country of Origin	Colombia
-------------------	----------

NMFC Code	069100-06
-----------	-----------

HTS Code	8421230090
----------	------------

UPC Code	742330043844
----------	--------------

EU Preferential Origin	No
------------------------	----

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that

accompanies the goods.