



## P552849

### LUBE FILTER, SPIN-ON FULL FLOW

#### Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

#### Attributes

Outer Diameter	75 mm (2.95 inch)
Thread Size	M20 x 1.5
Length	121 mm (4.76 inch)
Gasket OD	70 mm (2.76 inch)
Gasket ID	61 mm (2.40 inch)
Efficiency 99%	36 micron
Efficiency Test Std	SAE J1858
Anti-Drainback Valve	Yes
Bypass Valve	Yes

Bypass Valve Setting LR	0.8 bar (12 psi)
-------------------------	------------------

Bypass Valve Setting HR	1 bar (15 psi)
-------------------------	----------------

Media Type	Cellulose
------------	-----------

Collapse Burst	5.2 bar (75 psi)
----------------	------------------

Type	Full-Flow
------	-----------

Style	Spin-On
-------	---------

---

#### Packaged Dimensions

Packaged Length	0.28 FT
-----------------	---------

Packaged Width	0.28 FT
----------------	---------

Packaged Height	0.41 FT
-----------------	---------

Packaged Weight	0.65 LB
-----------------	---------

Packaged Volume	0.0309 FT <sup>3</sup>
-----------------	------------------------

---

#### Other Information

Country of Origin	Indonesia
-------------------	-----------

NMFC Code	069100-09
-----------	-----------

HTS Code	8421230090
----------	------------

UPC Code	742330044254
----------	--------------

EU Preferential Origin	No
------------------------	----

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that

accompanies the goods.