



P553771

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	3.66 inch (93 mm)
Thread Size	1-12 UN
Length	7.87 inch (200 mm)
Gasket OD	2.80 inch (71 mm)
Gasket ID	2.40 inch (61 mm)
Efficiency 99%	40 micron
Efficiency Test Std	ISO 4548-12
Anti-Drainback Valve	Yes
Bypass Valve	Yes

Bypass Valve Setting LR	29 psi (2 bar)
Bypass Valve Setting HR	36 psi (2.5 bar)
Media Type	Cellulose
Collapse Burst	100 psi (6.9 bar)
Type	Full-Flow
Style	Spin-On

Packaged Dimensions

Packaged Length	0.31 FT
Packaged Width	0.31 FT
Packaged Height	0.66FT
Packaged Weight	1.51 LB
Packaged Volume	0.0626 FT3

Other Information

Country of Origin	United States
NMFC Code	069100-09
HTS Code	8421230000
UPC Code	742330044445

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.