

Product Specifications



P554403

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	93 mm (3.66 inch)
Thread Size	3/4-16
Length	136 mm (5.35 inch)
Gasket OD	71 mm (2.80 inch)
Gasket ID	61 mm (2.40 inch)
Efficiency 99%	40 micron
Efficiency Test Std	SAE J806
Anti-Drainback Valve	Yes
Bypass Valve	Yes

Bypass Valve Setting LR	0.5 bar (7 psi)
Bypass Valve Setting HR	0.7 bar (10 psi)
Media Type	Cellulose
Collapse Burst	6.9 bar (100 psi)
Туре	Full-Flow
Style	Spin-On
Primary Application	PERKINS 2654403
Packaged Dimensions	
Packaged Length	3.94 IN
Packaged Width	3.94 IN
Packaged Height	5.51IN
Packaged Weight	1.3 LB
Packaged Volume	0.0495 FT3
Other Information	
Country of Origin	Poland
NMFC Code	133320
HTS Code	8421230090
UPC Code	742330044674
EU Preferential Origin	Yes

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the

© Donaldson Company, Inc.	chan danaldaan aam
actual country of origin and HS Code will be reflected on the Comme accompanies the goods.	ercial Invoice(s) that