



## P557207

### LUBE FILTER, SPIN-ON FULL FLOW

#### Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

#### Attributes

Outer Diameter	93 mm (3.66 inch)
Thread Size	1-12 UN
Length	174 mm (6.85 inch)
Gasket OD	71 mm (2.80 inch)
Gasket ID	61 mm (2.40 inch)
Efficiency 50%	20 micron
Efficiency 99%	40 micron
Efficiency Test Std	ISO 4548-12
Bypass Valve	Yes

Bypass Valve Setting LR	0.5 bar (7 psi)
Bypass Valve Setting HR	0.7 bar (10 psi)
Media Type	Cellulose
Collapse Burst	6.9 bar (100 psi)
Type	Full-Flow
Style	Spin-On
Primary Application	CASE/CASE IH 427207C2

---

#### Packaged Dimensions

Packaged Length	3.7 IN
Packaged Width	3.7 IN
Packaged Height	6.8IN
Packaged Weight	1.18 LB
Packaged Volume	0.0539 FT3

---

#### Other Information

Country of Origin	Mexico
NMFC Code	069100-06
HTS Code	8421230090
UPC Code	742330045374
EU Preferential Origin	No

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the

actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.