



P558250

LUBE FILTER, SPIN-ON FULL FLOW

Why Choose Donaldson Lube Filters?

Donaldson lube filters are designed to keep today's engine lube systems functioning at peak performance.

- Keep oil clean by capturing contaminants that cause engine damage.
- Include heavy duty components that are built to perform, built to last.
- Deliver essential engine protection for maximum cold flow performance.

Attributes

Outer Diameter	93 mm (3.66 inch)
Thread Size	1-12 UN
Length	172 mm (6.77 inch)
Gasket OD	71 mm (2.80 inch)
Gasket ID	61 mm (2.40 inch)
Efficiency 99%	40 micron
Efficiency Test Std	ISO 4548-12
Anti-Drainback Valve	Yes
Bypass Valve	Yes

Bypass Valve Setting LR	0.8 bar (12 psi)
Bypass Valve Setting HR	1.2 bar (17 psi)
Media Type	Cellulose
Collapse Burst	13.8 bar (200 psi)
Type	Full-Flow
Style	Spin-On
Primary Application	CASE/CASE IH 528250R91

Packaged Dimensions

Packaged Length	3.7 IN
Packaged Width	3.5 IN
Packaged Height	6.8IN
Packaged Weight	1.22 LB
Packaged Volume	0.05089868 FT3

Other Information

Country of Origin	Mexico
NMFC Code	069100-09
HTS Code	8421230090
UPC Code	742330045558
EU Preferential Origin	No

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the

actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.