

Product Specifications

LF16424



Lube, Cartridge

Fleetguard® LF16424 cartridge oil filter is environmentally friendly and features technology advances to achieve the high flow rates required by today's modern engine designs.

View product on Fleetguard.com

Specifications

Largest End ID	0.94 inch	Length	6.18 inch
Largest OD	1.99 inch	Efficiency Test Std	SAE J905
Media Type	Cellulose	Primary Particle Efficiency	13 micron (c) @ 70.9%
Rated Flow	0.8 L/m	Gasket Inside Diameter	0.94 inch
Test Specification	SAE J905	Gasket Hiside Diameter	0.94 IIICH

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs,

and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved