



Product Specifications

LF17502



Lube, By-Pass Spin-On

Fleetguard® LF17502 premium spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Gasket OD	4.02 inch	Length	10.24 inch
Largest OD	4.31 inch	Efficiency Test Std	ISO 4548-12
Pressure Valve	No	Media Type	Cellulose
Hydrostatic Burst Minimum	246.4999999999997 psi	Primary Particle Efficiency	16 micron (c) @ 98.7%
Rated Flow	10.8 L/m	Gasket Inside Diameter	3.70 inch
Test Specification	ISO 4548-12	Thread Size	1 3/8-16 UNF 2B

Product Comments

Compatible with Euro 6 oils

Related Parts

Upgrade Of LF3654
Is European Version Of LF3654

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved