



# Product Specifications

## LF3378



### Lube, Spin-On

Fleetguard® LF3378 lube combo spin-on filter combines full-flow and by-pass filtration into one single filter developed to meet or exceed engine requirements. This unique arrangement of filtration provides the perfect balance between efficiency and low restriction to oil flow.

[View product on Fleetguard.com](https://www.fleetguard.com)

### Specifications

Thread Size	3/4-16 UNF 2B	Media Type	StrataPore
Largest OD	3.68 inch	Length	3.62 inch
Gasket Inside Diameter	2.44 inch	Gasket OD	2.76 inch
Efficiency Test Std	ISO 4548-12	Pressure Valve	Yes
Hydrostatic Burst Minimum	1500 kPa	Pressure Valve Opening Pressure	250 kPa
Primary Particle Efficiency	50 micron (c) @ 98.7%	Rated Flow	30 L/m

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved