



# Product Specifications

## LF3536



### Lube, Full-Flow Spin-On

Fleetguard® LF3536 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](https://www.fleetguard.com)

## Specifications

Thread Size	M20X15-6H	Gasket Inside Diameter	2.26 inch
Gasket OD	2.52 inch	Length	4.02 inch
Largest OD	3.17 inch	Efficiency Test Std	ISO 4548-12
Primary Particle Efficiency	24.6 micron (c) @ 95%	Media Type	Cellulose

## Product Comments

For Fluted shell version, see LF16157.

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved