



Product Specifications

LF3654



Lube, By-Pass Spin-On

Fleetguard® LF3654 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Thread Size	1 3/8-16 UNF 2B	Gasket OD	3.94 inch
Gasket Inside Diameter	3.56 inch	Largest OD	4.24 inch
Length	10.39 inch	Primary Particle Efficiency	24.6 micron (c) @ 95%
Media Type	Cellulose		

Related Parts

For Upgrade, Use	LF17502
For European Version, Use	LF17502

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved