



Product Specifications

LF3716



Lube, Spin-On

Fleetguard® LF3716 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Thread Size	M20X1.5-6H	Largest OD	3.32 inch
Length	9.81 inch	Gasket Inside Diameter	2.26 inch
Gasket OD	2.52 inch	Hydrostatic Burst Minimum	203.0 psi
Pressure Valve	Yes	Rated Flow	10 L/m
Primary Particle Efficiency	24.6 micron (c) @ 95%		

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs,

and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved