



Product Specifications

LF3874



Lube

Fleetguard® LF3874 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Largest OD	2.91 inch	Length	3.31 inch
Hydrostatic Burst Minimum	256.00947456 PSI	Efficiency Test Std	ISO 4548-12
Rated Flow	10 L/m	Thread Size	3/4-16 UNF 2B
Primary Particle Efficiency	28 micron (c) @ 98.7%	Media Type	Cellulose

Related Parts

For European Version, Use LF3335

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved