

## **Product Specifications**

## LF4032



## Lube, Cartridge

Fleetguard® LF4032 cartridge oil filter is environmentally friendly and features technology advances to achieve the high flow rates required by today's modern engine designs.

View product on Fleetguard.com

## **Specifications**

| Largest OD                     | 3.62 inch   | Length                         | 5.65 inch             |
|--------------------------------|-------------|--------------------------------|-----------------------|
| Largest End ID                 | 0.51 inch   | Gasket Inside Diameter         | 0.98 inch             |
| Efficiency Test Std            | ISO 4548-12 | Pressure Valve                 | No                    |
| Element Collapse/Burst,<br>Min | 400 kPa     | Primary Particle<br>Efficiency | 57 micron (c) @ 98.7% |
| Rated Flow                     | 52 L/m      | Test Specification             | ISO 4548-12           |

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs,

and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved