



Product Specifications

LF700



Lube, Spin-On

Fleetguard® LF700 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Thread Size	3/4-16 UNF 2B	Gasket Inside Diameter	2.47 inch
Gasket OD	2.84 inch	Length	5.90 inch
Largest OD	3.02 inch	Pressure Valve	Yes
Hydrostatic Burst Minimum	203.0 psi	Rated Flow	14 L/m
Primary Particle Efficiency	24.6 micron (c) @ 68%		

Related Parts

Replaces LF3601

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor

completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Cummins Filtration Inc. All Rights Reserved