



# Product Specifications

## LF9008



### Lube

Fleetguard® LF9008 lube combo spin-on filter combines full-flow and by-pass filtration into one single filter developed to meet or exceed engine requirements. This unique arrangement of filtration provides the perfect balance between efficiency and low restriction to oil flow.

[View product on Fleetguard.com](https://www.fleetguard.com)

### Specifications

Media Type	StrataPore	Thread Size	1 1/2-12 UNF 2B
Length	9.91 inch	Largest OD	4.81 inch
Gasket Inside Diameter	3.89 inch	Gasket OD	4.41 inch
Hydrostatic Burst Minimum	426.2999999999995 psi	Rated Flow	77 L/m
Primary Particle Efficiency	24.6 micron (c) @ 98.7%		

### Product Comments

Stratapore Venturi Combo

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries

(collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved