



Product Specifications

LF9030



Lube, Spin-On

Fleetguard® LF9030 premium lube combo spin-on filter combines full-flow and by-pass filtration into one single filter developed to meet or exceed engine requirements. This unique arrangement of filtration provides the perfect balance between efficiency and low restriction to oil flow.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Thread Size	1.125-12 UNF 2B	Media Type	StrataPore
Largest OD	3.69 inch	Length	6.94 inch
Gasket Inside Diameter	2.46 inch	Gasket OD	2.83 inch
Hydrostatic Burst Minimum	203.0 psi	Pressure Valve	No
Rated Flow	33 L/m	Primary Particle Efficiency	24.6 micron (c) @ 100%

Related Parts

Replaces LF16164

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of

merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved