



Product Specifications

LF3325



Lube, Spin-On

Fleetguard® LF3325 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](https://www.fleetguard.com)

Specifications

Thread Size	1 1/2-12 UNF 2B	Gasket OD	4.36 inch
Gasket Inside Diameter	3.89 inch	Length	11.31 inch
Largest OD	4.74 inch	Media Type	Cellulose
Hydrostatic Burst Minimum	246.49999999999997 psi	Pressure Valve	No
Rated Flow	84 L/m	Primary Particle Efficiency	24.6 micron (c) @ 95%

Product Comments

For Use On Cummins KV16 Engines

Related Parts

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved